

# GOLF CLUB BAG

## BACKGROUND OF THE INVENTION

### 1. The field of the invention

[0001]The present invention generally relates to a golf club bag, and more particularly relates to a golf club bag comprising a first belt and a second belt that are engaged through a plurality of connecting elements for easy assembling and disassembling of the first belt and the second belt and easy and comfortable carriage of the golf club bag.

### 2. Description of the related art

[0002]Nowadays people enjoy a variety of sports after work for relaxing and exercising, for example, tennis, basketball, volleyball, baseball, golf, badminton and so on. Accordingly, various sports goods, such as bags, and sports outfit and shoes, are available in the market. Especially, the bag is designed to load many sports utensils, and the capacity of the bag is designed according to the feature of the sport and the number and size of the utensils. However, an ideal bag is one that features easy carriage, comfortable. More particularly, the golf clubs are longer, heavier and plural in number, accordingly, a golf club bag is designed to be larger. The golf club bag may be carried in a cart or on the user's back using a belt, and therefore, to design a golf club bag featuring convenience and comfortable for easy carriage is a top priority of the manufacturers. FIG. 4 shows a conventional golf club bag **A** having a belt **B**. The golf club bag **A** has a buckle **A1** at an upper portion and a buckle set **A2** at an outer flange of the lower portion thereof. The belt **B** is a long strap element with a buckle plate **B1** at a distal end buckling to the buckle **A1** of the golf club bag **A** and an elastic buckle **B2** at the primal end fixed

on the buckle set **A2** of the golf club bag **A**. However, there are some drawbacks of such conventional golf club bag as follows.

1. The belt **B** is fixed to the golf club bag **A** and only the elastic buckle **B2** has elasticity, and therefore it is inconvenient for the user to adjust the belt.
- 5 2. The belt **B** is fixed to the golf club bag **A** allowing the user to cross carry on the back, the weight of the golf club bag will be localized on one particular shoulder, and therefore, shoulder and back pain can easily occur while carrying.
3. The belt **B** cannot be separated from the golf club bag **A**, the weight and size of the golf club bag usually cause inconvenience to the user while removing the bag  
10 off the user's back.

[0003]Therefore, to seek for a solution to resolve the above drawbacks of the golf club bag is highly desirable.

## **SUMMARY OF THE INVENTION**

[0004]Accordingly, in the view of the foregoing, the present inventor makes a  
15 detailed study of related art to evaluate and consider, and uses years of accumulated experience in this field, and through several experiments, to create a new golf club bag in order to overcome the problems of the prior art.

[0005]According to a primary aspect of the present invention, the golf club bag is comprised of a first belt and a second belt, which are engaged to each other through a  
20 plurality of connecting elements, so that the first belt and the second belt of the golf club bag can be easily assembled and also for easy and comfortable carriage of the golf club bag.

[0006]According to another aspect of the present invention, a plurality of securing belt is arranged at an outer flange of the first and the second belt for adjusting the length of the belt according to the user's need.

## 5    **BRIEF DESCRIPTION OF THE DRAWING**

[0007]For a more complete understanding of the present invention, reference will now be made to the following detailed description of preferred embodiments taken in conjunction with the accompanying drawings, in which:

[0008]FIG. 1 is an exploded view of a belt of a golf club bag of the present  
10    invention;

[0009]FIG. 2 is an elevational view of the belt of the golf club bag of the present invention;

[0010]FIG. 3 is an elevational view of the golf club bag according to a preferred embodiment of the present invention; and

15    [0011]FIG. 4 is an elevational view of a conventional golf club bag.

## **DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS**

[0012]Reference will be made in detail to the preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer  
20    to the same or like parts.

[0013]Referring to FIGs. 1 and 2, show an exploded view and an elevational view of the belt of the golf club bag of the present invention respectively. The belt of the golf club bag of the present invention comprises a first belt 1 and a second belt 2.

[0014]The first belt 1 is a long arched strap, a soft pad 11 is disposed in the inner part of the first belt 1 and a connecting element 12 is disposed at one side thereof, wherein the connecting element 12 has a zipper 121 and an easy securing strap 122. Additionally, the first belt 1 has a plurality of securing strap 13 arranged at an outer flange thereof.

[0015]The second belt 2 is a long arched strap, a soft pad 21 is disposed in the inner part of the second belt 2 and a connecting element 22 is disposed at one side thereof, wherein the connecting element 22 has a zipper 221 and an easy securing strap 222. Additionally, the second belt 2 has a plurality of securing strap 23 arranged at an outer flange thereof.

[0016]To assemble the first belt 1 and the second belt 2 of the golf club bag of the present invention, the zipper 121 of the connecting element 12 of the first belt 1 is engaged with the zipper 221 of the connecting element 22 of the second belt 2. Next, the easy securing strap 122 of the connecting element 12 of the first belt 1 is fitted with the easy securing strap 222 of the connecting element 22 of the second belt 2, and further the plurality of securing strap 13 is secured with the outer flange of the first belt 1 and the plurality of securing strap 23 is secured with the outer flange of the second belt 2.

[0017]Referring to FIG. 3, the first belt 1 comprises a soft pad 11 and the second belt 2 comprises a soft pad 21 that are inlaid buckling to a plurality of buckle ring 31 of the golf club bag 3 by the securing belts 13 and 23 to enable the belt portion of the golf club bag 3 to secure tightly to the golf club bag 3 and also to provide comfort to the user while carriage.

[0018]The advantages of the golf club bag of the present invention are as follows.

1. The plurality of connecting elements **12** and **22** of the first belt **1** and second belt **2** are inlaid for fitting with each other or release from each other for easy and steady assembly.
2. The length of the first belt **1** and the second belt **2** can be shortened after  
5       disassembling for convenient carriage.
3. The plurality of securing straps **13** and **23** provides the feature of adjusting the length of the belt according to the user's need.

[0019] While the invention has been described in conjunction with a specific best mode, it is to be understood that many alternatives, modifications, and variations will be  
10       apparent to those skilled in the art in light of the foregoing description. Accordingly, it is intended to embrace all such alternatives, modifications, and variations in which fall within the spirit and scope of the included claims. All matters set forth herein or shown in the accompanying drawings are to be interpreted in an illustrative and non-limiting sense.